

Docket No. AUS920030935US1

DINING PREFERENCES STORAGE MECHANISM

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention relates generally to an improved data processing system and in particular to a method and apparatus for processing data. Still more particularly, the present invention relates to a method, apparatus, and computer instructions for managing user preferences with respect to food orders.

2. Description of Related Art:

In today's times, most people eat out at restaurants on a regular basis. In fact, many people eat out one or more times each week. When going to restaurants, especially fast food restaurants, the user selects different food items from a menu. In many cases, the user may alter the ingredients within a particular food item based on the user's preferences. In doing so, the user must recite or tell the restaurant employee their preferences on how they would like their food prepared. This communication of preferences is repeated each time an order is made even though the preferences may never change. If the preferences are lengthy or if the employee at the restaurant is in a hurry, some or all of the preferences may not be successfully recorded and fulfilled as desired by the user.

Additionally, some restaurants allow a customer to watch the preparation of the food. Before each

Docket No. AUS920030935US1

ingredient is added, the customer may be asked if that ingredient is desired. This type of preparation is commonplace in sandwich restaurants. The customer preferences on how to build a particular meal generally do not change, but the customer must repeat them each time the customer orders food from the restaurant.

Therefore, it would be advantageous to have an improved method, apparatus, and computer instructions for communicating user preferences for food items.

Docket No. AUS920030935US1

SUMMARY OF THE INVENTION

The present invention provides a storage device for dining preferences. The storage device includes a card, a memory, and a communications interface. The memory is located within the card. The memory stores a plurality of dining preferences for at least one restaurant. The dining preferences are portable from location to location and are capable of repetitious use. The communications interface allows for the dining preferences to be read from the memory by a data processing system at a restaurant for use in generating a food order.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a pictorial representation of a data processing system in which the present invention may be implemented in accordance with a preferred embodiment of the present invention;

Figure 2 is a block diagram of a data processing system in which the present invention may be implemented;

Figure 3 is a diagram illustrating a memory card in accordance with a preferred embodiment of the present invention;

Figure 4 is a diagram illustrating components used in storing and transferring dining preferences in accordance with a preferred embodiment of the present invention;

Figure 5 is a diagram illustrating an example of dining preferences in accordance with a preferred embodiment of the present invention;

Figure 6 is a flowchart of a process for communicating preferences for food items in accordance with a preferred embodiment of the present invention;

Docket No. AUS920030935US1

Figure 7 is a flowchart of a process for generating dining preferences in accordance with a preferred embodiment of the present invention; and

Figures 8A and **8B** are diagrams of an interface for displaying preferences from a memory card in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures and in particular with reference to **Figure 1**, a pictorial representation of a data processing system in which the present invention may be implemented is depicted in accordance with a preferred embodiment of the present invention. A computer **100** is depicted which includes system unit **102**, video display terminal **104**, keyboard **106**, storage devices **108**, which may include floppy drives and other types of permanent and removable storage media, and mouse **110**. Additional input devices may be included with personal computer **100**, such as, for example, a joystick, touchpad, touch screen, trackball, microphone, and the like. Computer **100** can be implemented using any suitable computer, such as an IBM eServer computer or IntelliStation computer, which are products of International Business Machines Corporation, located in Armonk, New York. Although the depicted representation shows a computer, other embodiments of the present invention may be implemented in other types of data processing systems, such as a network computer. Computer **100** also preferably includes a graphical user interface (GUI) that may be implemented by means of systems software residing in computer readable media in operation within computer **100**.

With reference now to **Figure 2**, a block diagram of a data processing system is shown in which the present invention may be implemented. Data processing system **200** is an example of a computer, such as computer **100** in

Docket No. AUS920030935US1

Figure 1, in which code or instructions implementing the processes of the present invention may be located. Data processing system **200** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used. Processor **202** and main memory **204** are connected to PCI local bus **206** through PCI bridge **208**. PCI bridge **208** also may include an integrated memory controller and cache memory for processor **202**. Additional connections to PCI local bus **206** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **210**, small computer system interface SCSI host bus adapter **212**, and expansion bus interface **214** are connected to PCI local bus **206** by direct component connection. In contrast, smart card adapter **216**, graphics adapter **218**, and audio/video adapter **219** are connected to PCI local bus **206** by add-in boards inserted into expansion slots. Expansion bus interface **214** provides a connection for a keyboard and mouse adapter **220**, modem **222**, and additional memory **224**. SCSI host bus adapter **212** provides a connection for hard disk drive **226**, tape drive **228**, and CD-ROM drive **230**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **202** and is used to coordinate and provide control of various components within data processing system **200** in **Figure 2**. The operating system may be a commercially available operating

Docket No. AUS920030935US1

system such as Windows XP, which is available from Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provides calls to the operating system from Java programs or applications executing on data processing system **200**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented programming system, and applications or programs are located on storage devices, such as hard disk drive **226**, and may be loaded into main memory **204** for execution by processor **202**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 2** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash read-only memory (ROM), equivalent nonvolatile memory, or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 2**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

For example, data processing system **200**, if optionally configured as a network computer, may not include SCSI host bus adapter **212**, hard disk drive **226**, tape drive **228**, and CD-ROM **230**. In that case, the computer, to be properly called a client computer, includes some type of network communication interface, such as LAN adapter **210**, modem **222**, or the like. As another example, data processing system **200** may be a stand-alone system configured to be bootable without relying on some type of network communication interface,

Docket No. AUS920030935US1

whether or not data processing system **200** comprises some type of network communication interface. As a further example, data processing system **200** may be a personal digital assistant (PDA), which is configured with ROM and/or flash ROM to provide non-volatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 2** and above-described examples are not meant to imply architectural limitations. For example, data processing system **200** also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system **200** also may be a kiosk or a Web appliance.

The processes of the present invention are performed by processor **202** using computer implemented instructions, which may be located in a memory such as, for example, main memory **204**, memory **224**, or in one or more peripheral devices **226-230**.

The present invention provides a method, apparatus, and computer instructions for communicating dining preferences of a customer to an establishment or business, such as a restaurant. A memory card or other storage device, such as a smart card, may be used to store preferences for various food items at one or more restaurants. This memory card is portable between different establishments.

In one illustrative example, when a customer orders food, the employee takes the card and transfers preferences for that particular restaurant into their order system. In this manner, preferences for a

Docket No. AUS920030935US1

particular meal may be automatically added to the order. These preferences may be recorded in the memory card in any number of different ways. For example, the customer may tell the employee preferences once and have those preferences saved on the card by the employee at the restaurant. Alternatively, a terminal may be provided at a restaurant or at other locations located remotely from the restaurant to allow users to set preferences. Also, a customer may set preferences at home or elsewhere through the use of a card reader attached to a personal computer or laptop.

The programming may occur using an interface, such as a Web interface in which the preferences are selected through a user entering data into a Web page. Such an interface is especially useful if the programming of the memory card is performed using a kiosk that is located in a public location, such as a bus terminal or a shopping mall. A user may program a card for different restaurants.

With reference next to **Figure 3**, a diagram illustrating a memory card is depicted in accordance with a preferred embodiment of the present invention. Smart card **300** is an example of one type of memory card that may be used to store user preferences for food items. These preferences include, for example, preferences for having or excluding certain items, such as mustard, tomatoes, mayonnaise, or cheese. Further, the preferences may include cooking preferences for meats, such as rare, medium, medium-well, and well done.

Docket No. AUS920030935US1

In this illustrative example, smart card **300** is a plastic card with embedded integrated circuits for storing this preference information. In particular, smart card **300** contains processor **302**, memory card **304**, and transceiver **306**. Smart card **300** is portable and resembles a credit card, but contains additional circuitry to store and process information. An alternative form of a memory card that may be used is a magnetic dashed stripe card. Such a card may be used, but stores less information and has no processing capability.

In this example, user preferences may be stored in memory **304**. These preferences may be accessed through processor **302**. The transmission of the preferences is provided through transceiver **306**. Transceiver **306** provides a contactless mechanism for transferring data. Such a system is less prone to errors than those types of smart cards requiring contact to transfer data. In this type of system, power is supplied to smart card **300** for processor **302** through battery **308**. Transceiver **306** provides a communications interface to send and receive data. This type of transceiver may use RF signals or infrared signals depending on the type of implementation.

This communications interface is used to exchange data with a data processing system, such as data processing system **200** in **Figure 2**. In particular, data may be exchanged through smart card adapter **216** in **Figure 2**. The smart card adapter provides a reader and writer to support various card protocols to allow reading and writing data to smart cards. The data processing system

Docket No. AUS920030935US1

may be, for example, a terminal at a restaurant, a home computer, or a kiosk.

Further, security protocols may be implemented using processor **302** to prevent writing data to memory **304** unless an appropriate key, such as a personal identification number (PIN) or certificate is received. In the illustrative examples, writing data to memory **304** is allowed without requiring entry of a key.

With respect to preferences stored in memory **304**, smart card **300** stores dining preferences for one or more restaurants in this memory. These preferences may be used through all different restaurants within a particular chain. Further, preferences stored in smart card **300** may be configured outside of a restaurant to indicate dining preferences for the different restaurants.

Smart card **300** may be read by a cash register system with a card reader to display preferences and initiate processing of a food order with the desired preferences. As a result, portability of dining preferences is provided for a customer in which these dining preferences may be carried to different restaurants through smart card **300**.

Turning now to **Figure 4**, a diagram illustrating components used in storing and transferring dining preferences is depicted in accordance with a preferred embodiment of the present invention. Smart card **400** contains dining preferences **402**. Smart card **400** may be implemented using a smart card, such as smart card **300** in **Figure 3**.

Docket No. AUS920030935US1

Dining preferences **402** are written to smart card **400** using preferences terminal **404**. Software, such as dining preferences generation process **406** is used to write the data to smart card **400**. Preferences terminal **404** may be implemented using a data processing system, such as data processing system **200** in **Figure 2**.

Preferences terminal **404** may be located in various locations, depending on the particular implementation. For example, preferences terminal **404** may take the form of a personal computer at the home of the customer or may be a kiosk in a mall or restaurant. Smart card **400** may be programmed at preference terminal **404** with preferences that may be used at a number of different restaurants, making these preferences portable for the user.

In these illustrative examples, the preferences may be entered by the customer. In another embodiment, preferences terminal **400** may be part of a food ordering system operated by an employee. In such a case, the employee may enter preferences for the user.

Dining preferences **402** may then be read at a later point in time by restaurant terminal **408**. In particular, order process **410** is software that is used to receive dining preferences **402** from smart card **400**. Restaurant terminal **408** may be implemented using a data processing system, such as data processing system **200** in **Figure 2**.

When dining preferences **402** are obtained by order process **410**, these preferences may be displayed on display **412**. In this manner, the user and employee both can verify that the preferences are the ones that the customer desires for a particular food item or order.

Docket No. AUS920030935US1

The food order may then be processed with the customer's particular dining preferences being taken into account. Dining preferences **402** may contain preferences for many different restaurants. In such a case, dining preferences **402** contains entries that may be identified in various ways, such as through a restaurant name, a meal name, or some other identifier along with the particular preferences for a particular meal or food item. As a result, smart card **400** is portable between different restaurants because smart card **400** is carried by the customer and preferences are stored in identification with a particular restaurant. Further, preferences programmed for a restaurant in one location may be used in restaurants in other locations that are part of the same chain in these illustrative examples.

With reference now to **Figure 5**, a diagram illustrating an example of dining preferences is depicted in accordance with a preferred embodiment of the present invention. Dining preferences **500** is an example of dining preferences, such as dining preferences **402** in **Figure 4** in this illustrative example. Dining preferences **500** is in an extensible mark up language (XML) format. Of course other types of schema or formats may be used depending on the particular implementation.

As illustrated, sections **502**, **504**, and **506** contain dining preferences for three different restaurants or establishments. In section **502**, line **508** identifies the restaurant name as "BurgerChain". Lines **510**, **512**, and **514** identify three food items for this particular

Docket No. AUS920030935US1

establishment. Sections **516**, **518**, and **520** contain the preferences for these three food items.

Next, line **522** identifies a different restaurant stored in the preferences. In this case, the restaurant is "CitySubSandwiches". Lines **524** and **526** identified two food items for this particular restaurant. The preferences for these food items are found in sections **528** and **530**. Line **532** identifies a third restaurant for the user preferences. This restaurant is named "Coffee Castle". The drink item is identified in line **534** with the preference for this drink item being specified in line **536**.

Turning now to **Figure 6**, a flowchart of process for communicating preferences for food items is depicted in accordance with the preferred embodiment of the present invention. The process illustrated in **Figure 6** may be implemented in a restaurant order process, such as order process **410** in **Figure 4**.

The process begins by detecting a smart card (step **600**). The smart card may be detected by contact with a card reader or through the smart card being within a selected proximity of the card reader. Dining preferences are requested from the smart card (step **602**). These dining preferences are received from the smart card (step **604**). Thereafter, the preferences are displayed (step **606**). This step displays the preferences and allows the customer and employee to verify that the preferences for a particular food order are correct. Thereafter, the food order is generated using the dining

Docket No. AUS920030935US1

preferences (step 608) with the process terminating thereafter.

Turning now to **Figure 7**, a flowchart of process for generating dining preferences is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 7** may be implemented in a process, such as dining preferences generation process 406 in **Figure 4**.

The process begins by displaying options (step 700). These options allow the user to create and edit dining preferences for different restaurants. A user input is received (step 702). A determination is then made as to whether the user input selects a preference (step 704). If a preference for a food item is selected, that preference is stored (step 706) with the process then returning to step 700.

In these illustrative examples, these preferences are for different preferences for food items. For example, a user may enter or select a preference, such as no mayonnaise, no ketchup, no pickles, and/or medium well. The different preferences that may be selected depend on the particular food item for which preferences are being generated.

With reference again to step 704, if the user input does not select a preference, then a determination is made as to whether user input selects an option to delete a preference (step 708). The user may wish to delete a preference that has just been selected or entered or change a previous preference. For example, previously, the user may have entered no tomatoes, but at this time

Docket No. AUS920030935US1

has decided that tomatoes are desirable for a particular food item. If the delete preference has been selected, the identified preference is deleted (step 710) with the process then returning to step 700.

With reference again to step 708, if the user input does not delete a preference, then a determination is made as to whether the user input selects an option indicating that the dining preferences are complete (step 712). If the dining preferences are not complete, the process returns to step 700. Otherwise, the stored preferences are written to the smart card (step 714) with the process then returning to step 700.

Turning next to **Figures 8A** and **8B**, diagrams of an interface for displaying preferences from a memory card is depicted in accordance with a preferred embodiment of the present invention. Displays **800** and **850** are examples of displays that may be presented at a terminal, such as preferences terminal **404** in **Figure 4**. This terminal may be located at different places, such as at a restaurant, in a public location, or at the user's home. Display **800** is presented when the memory card is read by the memory card reader at the terminal.

In **Figure 8A**, display **850** is an example of an initial display of preferences stored on a memory card, such as a smart card. These dining preferences illustrate those from preferences **500** in **Figure 5**. In display **850**, three restaurants, Burger Chain **852**, City Sub Sandwiches **854**, and Coffee Castle **856**, are shown. The preference information is displayed in a tree format in which additional information may be displayed by

Docket No. AUS920030935US1

selecting indicators **858**, **860**, and **862**. As can be seen, the following meals: roast beef **864** and chicken teriyaki **866** are displayed for City Sub Sandwiches **854** when indicator **860** is selected. A selection of the meal chicken teriyaki **866** results in a more detailed screen of the preferences for that meal being displayed.

In this illustrative example, in **Figure 8B**, display **800** is for a restaurant called City Sub Sandwiches. In this example, the meal is for a chicken teriyaki sandwich as shown in line **802**. This meal is displayed in response to a selection of chicken teriyaki **866** in display **850**. Section **804** in display **800** contains preferences for a chicken teriyaki meal as stored in section **530** in preferences **500** in **Figure 5**.

If the user is satisfied with the preferences, as shown in display **800**, the user may select "Okay" button **806**. If the terminal for display **800** is a cash register located at a restaurant, selection of this button causes an order to be generated using these preferences. If the user desires to change preferences, the user may select "Change" button **808**. Selection of this button will allow the user to edit text within section **804** to add, delete, and/or change preferences. If the user wishes to cancel the transaction, the user may select "Cancel" button **810**.

Thus, the present invention provides an improved method, apparatus, and computer instructions for generating and communicating dining preferences for a customer. The mechanism of the present invention stores dining preferences for one or more restaurants in a portable storage device, such as a smart card. In these

Docket No. AUS920030935US1

examples, the preferences are communicated by the smart card to the ordering system of the particular restaurant for which a food item is desired. The portable storage device allows portability of the preferences from one restaurant to another restaurant. Preferences generated for one restaurant may be used in other restaurants in the same chain of restaurants. Further, preferences may be present for different restaurants.

In this manner, dining preferences for a user may be quickly and efficiently transmitted to a restaurant. In this manner, fewer errors are likely to be made in taking and filling food orders. Further, by transmitting these dining preferences using a smart card, the time needed for a user to verbally communicate the same dining preferences is avoided. As a result, ordering of food at a restaurant becomes more efficient and pleasant for customers.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog

Docket No. AUS920030935US1

communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.